

Replacing and Installing a New Handle Assembly

| Step | Description | Tools | Picture |
|------|---|--|--|
| | This guide covers how to install a handle bracket (full assembly, lower handles, and handle brackets). The guide applies to all portable Lobster Tennis and Pickleball machines. | Phillips Screw driver, ½' long Phillips screw with short handle, Needle nose pliers. | |
| 1 | Remove the red case by unscrewing the (6) phillips-head screws along the bottom of the machine. There are (2) screws on the front and rear, as well as (1) on each side. | Phillips Screw Driver | Case Screws (Front & Rear) |
| 2 | Gently lift up the case being careful not to disconnect any wires. Rest the case next to the machine. | | Case Removed |
| 3 | (Installing Lower handles, or Fully Handle Assembly) Unscrew the 4 screws holding in the lower the handle on the left and right sides of the battery. Once they are out-slide the lower handles away from the machine (pull toward you). (This section applies to Both the Elite A through Elite 5-LE models, as well as the Pickle and Pickle 2). | Screw gun with Philips head. | Lower Handle screws on the right and left side of the batter |



Repair Instructions Replacing and Installing a New Handle Assembly

| | Replacing and Installing a New Handle A | ssembly | | |
|---|--|--|---|------------------|
| 4 | Slide your new Lower Handles into the slots where you took your old lower handles out. (To the left and right sides of your battery). Screw in the 4 screws to secure the assembly. (This section applies to Both the Elite Liberty through Elite 5-LE Tennis ball machines, and Pickleball machine models). NOTE: If you have an older machine with metal brackets, you will need to purchase the Upper handle Assembly, item E508.A, as we no longer carry the metal handle brackets. | Screw gun with Philips head. | Push New Lo Assembly into s screws to tight | ots, and use the |
| 5 | (Bracket Installation for Elite All Models) With the new lower handles in place- make sure you slide the Single Button Connector down to 2 nd hole- with both "buttons" facing inside the handles. | Pliers | Single Button c "Buttons" fac | ing inside the |
| 6 | (Bracket Installation for All Models) You will have two sets of plastic handle brackets. Both handle brackets come with a gold spacer, and 2 plastic sides. Starting with the Left side of the lower handle, take Bracket A1 and fasten the small screw through opening C. Tighten the golden spacer to the small screw. Now slide port A and B through the upper handle (left side), and C through the top hole of the Lower Handle. | ½" long Phillips screw driver. (with short handle). | Port A B C Left Handle assert | |
| 7 | (Bracket Installation for All Models) Now take bracket B1 and the small screw, and using your ½" phillips screw driver, screw through hole C, connecting Bracket A1 and B1 to each other by the golden spacer. Using holes A and B on bracket B1, screw the 2 larger screws into the plastic until they are flush with the plastic bracket. | 1/2" long Phillips screw driver. (with short handle). | | A B C |



Replacing and Installing a New Handle Assembly

| | | ½″ long | Elite handle Bracket Assembly completed. |
|---|--|-----------------------------|---|
| 8 | (Bracket Installation for All Models) Follow the same instructions for the right handle be assembly- when that is finished it should look like the right. | Phillips screw | Handle Bracket button switches facing the inside of the Handle. |
| 9 | Place the red case back on to the machine and reat the (6) screws along the bottom of the red case. | Phillips Screw Driver | Case Screws (Front & Rear) Case Screws (Side) |
| | Replacement Parts: EAHB2 Elite Handle Brackets E506 Upper Handle Assembly E508.A Lower Handle Assembly EAH2 Full Handle Assembly E508.A Upper Handle with brackets | · | |

Repair Instructions



| Replacing and Installing a New Handle Assembly |
|--|
|--|

| replacing and incoming a record and incoming |] |
|--|---|
| | |
| | |
| | |
| | |